



PCT/CH 2004/000505

REC'D 2 4 AUG 2004

WIPO PCT

The Patent Office Concept House Cardiff Road Newport South Wales NP10 800

CH04/505

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

egistration under the Companies Act does not constitute a new legal entity but merely cts the company to certain additional company law rules.

۰.,٠

Signed

Dated

12 May 2004

BEST AVAILABLE COPY

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)



atents Act 1977 tule 16)

THE PATENT OFFICE Patent D Patent Office 18 AUG 2003

1/77

Request for grant of a patent

See the notes on the back of this form. You can also get n explanatory leaflet from the Patent Office to help ou fill in this form) The Patent Office

Cardiff Road Newport South Wales NP10 8QQ

•	Your reference		30094GB	18AUG03 E830877-1 D10149 P01/7700 0.00-0319277-0
: .	Patent application number (The Patent Office will fill in this part)	031	9277.0	18 AUG 2003
3.	Full name, address and postcode of the or each applicant (underline all surnames)	r of	Givaudan SA Chemin de la 1214 Vernier Switzerland	
 -	Patents ADP Number (if you know it)			8408031001
	If the applicant is a corporate body, give country/state of its incorporation	the	Switzerland	
1.	Title of the Invention		COMPOUNDS	
 5.	Name of your agent (if you have one)	<u> </u>		
	"Address for service" in the United Kingo to which all correspondence should be s (including the postcode)		Centre for Inno 76-80 Church S Middlesex TW1 United Kingdon	8 4XR
	Patents ADP number (if you know it)			\$ CATS 1200 1
б.	If you are declaring priority from one or earlier patent applications, give the counand the date of filing of the or of each of earlier applications and (if you know it) the each application number	ntry these	Country	Priority application number Date of filing (if you know it) (day/month/year)
7.	If this application is divided or otherwis derived from an earlier UK application, give the number and the filing date of the earlier application	е	Number of earlier	application Date of filing (day/month/year)
8.	Is a statement of inventorship and of rist of grant of a patent required in support of this request? (Answer 'Yes' if:) a) any applicant named in part 3 is not an inventob) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d)	t .	yes	

Pates Form 1/77

 Enter the number of sheets for any of the following items you are filing with this form.
 Do not count copies of the same document

Continuation sheets of this form

Description 9

Claim(s) 3

Abstract 1

1

Drawing(s)



10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We

I/We request the grant of a patent on the basis of this application.

Signature

Date 14/08/03

 Name and daytime telephone number of person to contact in the United Kingdom

Colin Brown (office time) Tel. No: 01/784417721

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office

COMPOUNDS

This invention relates to a method of preparing methylaluminium dichloride and to its use in the preparation of certain fragrant substances.

5

Methylaluminium dichloride (MADC) was characterised and procedures for its preparation were published some time ago (for example, *J.Org.Chem.* 5, 106 (1940)). Several later publications described its preparation (for example, *J.Am.Chem.Soc.* 73, 2854 (1951) and US 2,712,546).

10

MADC is potentially useful as a Lewis acid in syntheses, but its use has been hindered by the fact that is is difficult to make consistently and inexpensively on an industrial scale (see, for example, Houben-Weyl "Methoden der organischen Chemie" (Thieme Verlag, 1970), Bd 13/4, pp.59-78).

15

It has now been found that it is possible to prepare MADC by a cheap, efficient process that gives a good yield of the compound. It has the additional advantage that the unpurified compound as prepared can be used directly in the preparation of desirable organic compounds. The invention therefore provides a process for the preparation of MADC comprising the steps of

20

(i) reacting by heating a material of the formula R₃Al₂X₃, where R is C₁-C₄ alkyl and X is selected from bromine and iodine, with an aluminium-containing material selected from metallic aluminium and a mixture of metallic aluminium and aluminium trichloride in an atmosphere of methyl chloride, with the proviso that, when R is methyl and X is iodine, the aluminium-containing material is a mixture of aluminium and aluminium trichloride; and

25

(ii) when the aluminium-containing material is metallic aluminium, adding aluminium trichloride to this reaction mixture and heating,

to give a crude reaction product; and

(iii) if desired, obtaining methylaluminium dichloride from this crude reaction product.

The compound of formula R₃Al₂X₃ as hereinabove defined (hereinafter "the sesquihalide") may be any such material, but it is preferably selected from methylaluminium sesquiiodide (MASI) and ethylaluminium sesquibromide (EASB). The sesquihalide may be a pure material, but it is preferably the crude mixture of unreacted raw materials and product resulting from the preparation method described by Grosse and Mativy in *J.Org.Chem.* 5, 106 (1940). This describes the MASI preparation, (in this case, the mixture is aluminium, unreacted methyl iodide and MASI), but EASB and the other sesquihalides may be prepared by an exactly analogous method.

This crude sesquihalide mixture is added directly to an aluminium-containing material. The aluminium-containing material is preferably metallic aluminium in particulate form, more preferably it is aluminium gritty. An example of a suitable material is FlukaTM 11008 in the Sigma-Aldrich Catalogue. The aluminium-containing material may also be a mixture of metallic aluminium and aluminium trichloride. When the sesquihalide is MASI, the aluminium-containing material must be such a mixture. The weight ratio of Al to AlCl₃ is preferably from 2:1 to 3:1.

20

The method comprises the following steps:

- (i) the crude sesquihalide mixture is sprinkled over the aluminium-containing material in an atmosphere of methyl chloride at a pressure of 1 bar, and the mixture heated; and then
- 25 (ii) when the aluminium-containing material is metallic aluminium, the aluminium chloride is added and the mixture is again heated.

Naturally, when the aluminium-containing compound is an aluminium/aluminium trichloride mixture, step (ii) above is unnecessary.

The following reaction conditions are typical and are given by way of guidance only – the skilled person will know what adjustments will be necessary in each case. Although they are described with reference to the preferred MASI and EASB, the same principles apply for the preparation of all sesquihalides.

5

The reaction conditions needed to start the reaction are slightly different, depending on whether MASI or EASB will be used. The starting temperature for MASI may be room temperature (20°-25°C), but slight heating may be needed in the case of EASB (about 45°C). From this point on, the conditions are similar; the temperature is raised to about 115°-120°C and maintained there for 4-6h. At this point, the temperature is lowered to 60°-70°C, and non-polar solvent, typically toluene or cyclohexane, may be added, if need be.

The yield in both cases is typically at least 75% MADC, based on the weight of the aluminium-containing material.

15

The proportions of crude sesquihalide used are from 0.2-20%, preferably from 0.5-5% by weight of the aluminium-containing material. Without restricting the invention in any way, it is believed that the sesquihalide acts as an activator for the aluminium. It is preferred not to exceed 10% purely for cost reasons – more can be used, but it has no greater effect.

20

If desired, pure MADC may be produced from the resulting crude MADC by distillation.

However, in another aspect of this invention, this crude MADC may be used in this form to promote a desirable organic reaction. Thus, the invention also provides a method of producing β-Georgywood, comprising the addition of pseudo-Georgywood (ψ-Georgywood) to the abovementioned crude MADC.

β-Georgywood (cis-2-acetyl-1,2,3,4,5,6,7,8-octahydro-1,2,8,8-tetramethylnaphthalene) is a

fragrance ingredient having the formula I:

This fragrant material is described in United States Patent 5,707,961. It is known from this patent that Compound Immay be prepared by the cyclisation of ψ-Georgywood (cis-1-[1,2-dimethyl-4(4-methyl-pent-3-enyl)-cyclohex-3-enyl]-ethanone – Formula II):

The method of preparing the compound of Formula I from that of Formula II is described in paragraph (d) of Example 1 of the abovementioned US patent. However, that preparation gives a mixture of Compound I and its structural isomer *iso*-Georgywood, shown in Formula III:

Ш

The compound of Formula I has particularly desirable olfactory properties. It is therefore desirable to increase the proportion of the compound of Formula I in the mixture. Achieving this using the technology of US 5,707,961 is very difficult.

The process of preparation of β -Georgywood according to the present invention gives a number of distinct advantages:

The compound of Formula I is obtained in a yield of more than 80% and in a purity of
 higher than 90%. The compound of Formula III is present only in trace amounts (less than 1%).

251FE.

2. The reaction can be carried out as a "one pot" reaction, that is, all the reactions from the initial MADC preparation to the final product reaction can be carried out in a single reaction vessel, without the need to isolate and purify intermediates.

Both of these are of considerable significance to the preparation of β -Georgywood on a commercial scale.

- 15 A further advantage of the method of this invention is that the compound of Formula I made by the abovementioned process can be easily decoloured, something that is difficult to achieve with products obtained from iodine-containing reagents. For example, a product obtained using MASI as starting material is easily decoloured by stirring or distilling over an acidic clay. In this regard, the product obtained by using EASB as starting material is even better, in that
- 20 decolorisation is not necessary.

The process is carried out simply by adding Compound II to the crude MADC and heating for about 4 hours at about 60°-70°C.

25 The invention is further described with reference to the following non-limiting examples.

Example 1: Preparation of crude MASI, crude MASC and MADC (distilled)

Under nitrogen 18.2g (0.13 mol) methyl iodide and 2g (0.75 mol) aluminium gritty (FlukaTM 110008) are heated to reflux (45°C) for 8-12 h. The resulting crude MASI reaction 5 mixture can be stored under nitrogen for several weeks without loss of activity.

16.2g (0.6 mol) aluminium gritty (Fluka 11008) is placed under 1 atm of methyl chloride (dried over a column filled with KOH) in a sulphonation flask equipped with a reflux condenser and a balloon fixed on the gas-outlet. 0.4ml (ca. 5% w/w) of the above aluminium/methyl iodide/MASI mixture is sprinkled via syringe over the aluminium at 90°C. The reaction starts with a temperature rise to 120°C and formation of liquid MASC. Under stirring, the reaction temperature is maintained at 120°C for 4h (by means of slight cooling and regulation of the methyl chloride flow) until the exothermy and the methyl chloride uptake (56g, 1.1 mol) cease and the theoretical volume of 54ml (d = 1.15) liquid MASC is reached.

The methyl chloride atmosphere is replaced by nitrogen. The black liquid is cooled to 60°C, at which point 29 g (0.22 mol) aluminium chloride is added via a nitrogen-flushed proportioning screw. The black suspension is heated to 120°C and maintained there for 30 min. Formation of MADC can be checked by briefly cooling to under 55°C, at which temperature the reaction mass solidifies. The proportioning screw is replaced by a distillation bridge and the MADC is distilled under 1 atm of nitrogen at bpt. = 157°C to give 69.3g (75% based on aluminium and aluminium trichloride) of colourless MADC, which crystallizes at room temperature in long white needles.

Analytical data:

25 MASI (crude): 27 Al-NMR (neat): 71 (W_{1/2}= 14800 Hz) ppm.

MASC (crude): 27 Al-NMR (hexane): 177 (W_{1/2}= 7600 Hz), 136 (W_{1/2}= 6000 Hz) ppm.

MADC (dist): Fp = 73°C, bp = 157°C. ²⁷Al-NMR (hexane): 136 (W_{1/2} = 6000 Hz) ppm.

Cyclization of pseudo-Georgywood (ψ-Georgywood) with commercial MADC: Example 2: (cis-2-acetyl-1,2,3,4,5,6,7,8-octahydro-1,2,8,8-tetramethylnaphthalene (B-Georgywood)

20g (85 mmol) ψ-Georgywood dissolved in 100g toluene is added under ice cooling to 5 157g (0.21 mol) MADC (1 M in hexane, AldrichTM 29680-5). The mixture is heated to 70°C for 2-3h, then quenched under ice-cooling with 40g ethanol, then with 2M HCl. The organic phase is separated and the aqueous phase extracted with t-butyl methyl ether. The combined organic layers are washed with conc. NaCl, then with water until pH = 7. The organic phase is dried 10 over MgSO₄, filtered and concentrated under reduced pressure. The residue is distilled over a short Vigreux column (124°C/0.1 Torr) to give 16g (80%) of β-Georgywood as a colorless liquid (GC purity ~ 90%).

Analytical data:

15

IR (film): 2930 m, 1700 s (C=O), 1560 m, 1377 m, 1357 m, 1240 w, 1220 w, 1090 m.

GC/MS: 234 (25%, $[M]^+$), 219 (15%, $[M - CH_3]^+$), 191 (100%, $[M - Ac]^+$, 161 (20%), 135 (65%), 121 (40%), 105 (40%), 91 (30%), 69 (30%), 43 (55%).

20

 1 H-NMR (CDCl₃, 400 MHz): 0.85 (d, 3H, J = 6.9 Hz, C1-Me), 0.99 (s, 3H), 1.02 (s, 3H), 1.06 (s, 3H), 1.4-2.2 (10 H, 5 CH₂), 2.15 (s, 3 H, Ac-Me), 2.36 (q, 1 H, <math>J = 6.9 Hz, C1-H) ppm.

¹³C-NMR (CDCl₃, 400 MHz): 19.1 (CH₂), 19.7 (CH₃), 21.0 (CH₃), 22.5 (CH₂), 24.9 (CH₃), 27.7 25 (CH₂), 28.9 (CH₃), 29.4 (CH₃), 30.8 (CH₂), 34.0 (C), 35.4 (CH), 40.1 (CH₂), 50.7 (C), 125.9 (C=), 136.9 (C=), 214.5 (C=O) ppm.

Example 3: Cyclization of pseudo-Georgywood with crude MADC via MASI activation of aluminium in the presence of AlCl₃: β-Georgywood

1.5ml (ca. 0.013 mol) of the aluminium/methyl iodide/MASI mixture prepared according to example 1 is sprinkled via syringe onto a stirred mixture of 42.9g (1.59 mol) of aluminium gritty (FlukaTM 11008) and 105.0g (0.79 mol) of aluminium trichloride flakes (Fluka 06220) under 1 atm of methyl chloride at room temperature. The reaction starts almost at once and the initially solid reaction mixture progressively turns into a liquid. The methyl chloride absorption rate is kept approximately constant by gradually increasing the temperature from 25 to 120°C over the next 2h. The reaction is then allowed to proceed at 120°C until no more gas absorption is observed (about 1h). This happens after about 156.0g (3.09 mol) of methyl chloride has been consumed. The crude molten MADC is cooled down to 70°C, the methyl chloride atmosphere is exchanged for an argon one and 810g of dry toluene is added.

The ca. 25 wt% suspension of crude MADC in toluene thus obtained is cooled to 10-15°C and 275.0g (1.06 mol) of 90% pure pseudo-Georgywood is added dropwise. The mixture is heated at 70°C until nearly complete cyclization of pseudo-Georgywood is detected by GC (about 2-3h). The reaction mixture is cooled to 0°C and pumped via a double-tipped needle on to 1.8 kg of ice-cooled 5% aqueous hydrochloric acid. The organic layer is separated, washed until neutral and refluxed for 2h over 30.0g of Montmorillonite K10, an acidic clay. Filtration and concentration of the organic layer under reduced pressure gives crude β-Georgywood, which is rectified over 3 weight% of Montmorillonite K10 through a 2.5 x 20 cm Vigreux column (105-110°C/1 mbar) to give 227g (82.5 % based on pseudo-Georgywood) β-Georgywood (GC-purity 86%) of a yellow colour.

25

Two further distillations over 10 weight% of paraffin oil and 3 weight% of Montmorillonite K10 give nearly colorless β-Georgywood.

Analytical data: Identical with those from example 2.

Example 4: Cyclization of pseudo-Georgywood with crude MADC via EASB activation of aluminium in the presence of AlCl₃: β-Georgywood

10.0g (0.37 mol) of aluminium gritty (FlukaTM 11008) suspended in 87.7g (0.81 mol) of 5 ethyl bromide is refluxed for 18 hours at 40°-65°C under nitrogen atmosphere. The crude EASB reaction mixture thus obtained can be stored under nitrogen atmosphere for several weeks without any loss of activity.

A stirred mixture containing 47.1g (1.75 mol) of aluminium gritty (Fluka 11008) and 115.5 g (0.87 mol) of aluminium trichloride flakes (Fluka 06220) is heated for 30 minutes at 40-45°C under 1 atm of methyl chloride. At this temperature, 9ml (ca. 0.05 mol) of the above-prepared crude aluminium/ethyl bromide/EASB mixture is sprinkled via syringe on to the contents of the vessel and the reaction starts almost at once. The methyl chloride absorption rate is kept approximately constant by gradually increasing the temperature from 45 to 120°C over the next 3h and the initially solid reaction mixture progressively turns into a liquid. The reaction mixture is then heated for a further 3h at 120°C, during which period of time gas absorption stops after an average amount of 186.0g (3.69 mol) of methyl chloride has been consumed. The crude molten MADC is cooled to 70°C, the methyl chloride atmosphere is exchanged for an argon one and 810g of dry toluene is added.

20

The ca. 27 wt% suspension of crude MADC in toluene thus obtained is cooled to 10-15°C and 275.0g (1.06 mol) of 90% pure pseudo-Georgywood is added dropwise. The mixture is heated to 70°C until nearly complete cyclization of pseudo-Georgywood is detected by GC (about 4 h). The reaction mixture is cooled to 0°C and pumped via a double-tipped needle on to 1.8 kg of ice-cooled 5% aqueous hydrochloric acid. The organic layer is separated, washed until neutral and concentrated under reduced pressure to give crude β-Georgywood which is rectified through a 2.5 x 31 cm Sulzer DX type column (105-110°C / 1 mbar) to give 224.5 g (82%) β-Georgywood (GC purity 89%).

Analytical data: Identical with those from Example 2.


Claims:

15

- 1. A process for the preparation of methylaluminium dichloride by the steps of
- (i) reacting by heating a material of the formula R₃Al₂X₃, where R is C₁-C₄ alkyl and X is selected from bromine and iodine with an aluminium-containing material selected from metallic aluminium and a mixture of metallic aluminium and aluminium trichloride in an atmosphere of methyl chloride, with the proviso that when R is methyl and X is iodine, the aluminium-containing material is a mixture of aluminium and aluminium trichloride; and
 - (ii) when the aluminium-containing material is metallic aluminium, adding aluminium trichloride to this reaction mixture and heating,

to give a crude reaction product; and

- (iii) if desired, obtaining methylaluminium dichloride from this crude reaction product.
- A method according to claim 1, in which the material of the formula R₃Al₂X₃ is selected
 from methylaluminium sesquiiodide and ethylaluminium sesquibromide.
 - 3. A method of preparing a compound of the Formula I



comprising the addition of a compound of Formula II

to the crude reaction product of a reaction according to Claim 1.

5 4. — Use-in-the-preparation-of-a compound-of-Formula-I

by cyclisation of a compound of Formula II

of a reaction mixture prepared by the steps of

10

(i) reacting by heating a material of the formula R₃Al₂X₃, where R is C₁-C₄ alkyl and X is selected from bromine and iodine with an aluminium-containing material selected from metallic aluminium and a mixture of metallic aluminium and aluminium trichloride in an atmosphere of methyl chloride, with the proviso

that when R is methyl and X is iodine, the aluminium-containing material is a mixture of aluminium and aluminium trichloride; and

(ii) when the aluminium-containing material is metallic aluminium, adding aluminium trichloride to this reaction mixture and heating.

. . .

ABSTRACT

A process of preparing methylaluminium dichloride by

- 5 (i) reacting by heating a material of the formula R₃Al₂X₃, where R is C₁-C₄ alkyl and X is selected from bromine and iodine with an aluminium-containing material selected from metallic aluminium and a mixture of metallic aluminium and aluminium trichloride in an atmosphere of methyl chloride, with the proviso that when R is methyl and X is iodine, the aluminium-containing material is a mixture of aluminium and aluminium trichloride; and
 - (ii) when the aluminium-containing material is metallic aluminium, adding aluminium trichloride to this reaction mixture and heating,

to give a crude reaction product; and

- (iii) if desired, obtaining methylaluminium dichloride from this crude reaction product.
- The crude reaction product may be used directly in organic syntheses, such as the cyclisation of ψ-Georgywood to give β-Georgywood.

15

PCT/**CH**20**04**/000**505**

:

j

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:			
BLACK BORDERS			
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES			
FADED TEXT OR DRAWING			
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING			
☐ SKEWED/SLANTED IMAGES			
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS			
GRAY SCALE DOCUMENTS			
LINES OR MARKS ON ORIGINAL DOCUMENT			
\square reference(s) or exhibit(s) submitted are poor quality			

IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.